

starting position to the predicted position, and further moving the
executing device to the predicted position, from a position of the
executing device after the above further moving used as the retrieval
starting position, so as to check whether the special detected signal is
5 detected or not. In addition, in the retrieving process, the setting area
adjacent to the setting area where the special detected signal detected
last is recorded, is regarded as the non-used setting area, when none
of the special detected signal is detected while the executing device is
moved from the retrieval starting position to the predicted position.

10 According to this aspect, since a non-used setting area is
detected based on the special detected signal while repeating the
transition of the executing device from the retrieval starting position to
the predicted position and the update of the retrieval starting position,
it is possible to detect the non-used setting area accurately.

15 In further aspect of the present invention, the recording
parameter is intensity of an optical beam for use in the information
recording.

According to this aspect, use of a non-used setting area enables
the accurate setting of the intensity of the recording optical beam.

20 In further aspect of the present invention, the method is further
provided with a recording process for executing the information
recording by use of the set recording parameter.

The above object of the present invention can be achieved by an
information recording medium of the present invention in which a
25 setting program is recorded in a readable way by a setting computer,
which is included in a recording parameter setting apparatus for
setting a recording parameter for use in optical information recording

on the recording medium, using any one of a plurality of setting areas previously provided on the recording medium. The setting program causes the setting computer to function as: a checking device for checking whether a special detected signal is optically detected or not
5 from the setting areas; a retrieving device for retrieving a non-used area that is the setting area where no special detected signal is detected, of the setting areas, based on the check result of the checking device; a mark signal recording device for optically recording a mark signal for obtaining the special detected signal optically, in the
10 detected non-used setting area; a setting signal recording device for recording a setting signal for setting the recording parameter, at least, in the non-used setting area excluding an area where the mark signal is recorded; and a setting device for setting the recording parameter by optically detecting the recorded setting signal.

15 According to the present invention, since the setting computer works so as to retrieve a non-used setting area by referring to the special detected signal to record the mark signal and the setting signal and so as to set the recording parameter by use of this recorded setting signal, it is possible to retrieve the non-used setting area accurately
20 and set the recording parameter accurately by use of this. Therefore use of the accurately-set recording parameter enables the accurate and assured information recording.

In one aspect of the present invention, the mark signal recording device records the mark signal at a position detected prior to the
25 setting signal recorded in the non-used setting area.

According to this aspect, since the setting computer works so as to record the mark signal at a position detected prior to the setting

signal, the accurate detection of the first detected position in the setting area enables accurate detection of a non-used setting area.

In another aspect of the present invention, the mark signal recording device repeats the recording of the mark signal at a predetermined interval during the recording of the setting signal.

According to this aspect, since the setting computer works so as to record the mark signal at a predetermined interval during recording the setting signal, it is possible to prevent from a detection mistake of a non-used setting area caused by detecting no special setting signal for a long time.

In further aspect of the present invention, the checking device is further provided with: a position retrieving device for retrieving a predicted position of the setting area on the recording medium where the special detected signal is to be optically detected; a first moving device for moving an executing device for detecting the setting signal and the special detected signal, from the retrieved predicted position, to a retrieval starting position on the recording medium distant from there at least by a distance corresponding to the predetermined interval; and a second moving device for repeating an operation of further moving the executing device again from the special detected signal-detected position on the recording medium to a position on the recording medium distant from there at least by a distance corresponding to the predetermined interval, when the special detected signal is detected while the executing device is moved from the retrieval starting position to the predicted position, and further moving the executing device to the predicted position, from a position of the executing device after the above further moving used as the retrieval